

How to Determine Strike Lip Length for Greater Than 1-3/4" Thick Doors

Door Hand	Extended Equally (EE)	Extended Inside (EI) Extended from 1-3/4" thick base door	Extended Outside (EO)	Extended Differently (ED)
Right Hand (RH) or Left Hand (LH)	$(\text{Door Thickness} + 2) + 1/4"$	Standard lip length + extended thickness	Standard lip length	Distance from center of latch to inside + 1/4" (use EO if distance from center of latch to inside is 7/8")
Right Hand Reverse (RHR) or Left Hand Reverse (LHR)	$(\text{Door Thickness} + 2) + 1/4"$	Standard lip length	Standard lip length + extended thickness	Distance from center of latch to outside + 1/4" (use EI if distance from center of latch to outside is 7/8")

Strike Lip Length Availability (round up as necessary)

Strike	Lip Lengths	Standard for:	Option for:	Up to 6" lip lengths available special per:
10-001 T-Strike	1" 1-1/8" (std. for 1-3/4" doors) 1-1/4" 1-1/2" 1-3/4" 2"	"A" B200 "F" w/ "NF" suffix "H" "S"	"E/B" "F"	XQ03-493
10-013 T-Strike	1-1/8" (for 1-3/4" doors) 1-1/2"		"A", B200, "D", "E", "H"	XQ03-494
10-025 ANSI Cylindrical	1-3/16" (std. for 1-3/4" doors) 1-3/8"	"C" & "D"	"A", B200, "E", "F", "S"	XQ07-351
10-072 ANSI Mortise	1" 1-3/16" (std. for 1-3/4" doors) 1-1/2" 1-3/4" 2"	"L"		XK10-992 (7/8" lip length available per XK11-437)

Note: Full lip strikes (standard for "F", "E/B" and "MD/ME") are only available 1-1/8" lip to center.